



P810

- Direct USB charging by power bank/computer
- Long lasting battery life (2000Mah)
- Support IOS app and Android device connection
- Support Bluetooth connection
- Large paper roll capacity(diameter 50mm)

APPLICATIONS



Shopping



Mart



Hospital



Coffee Shop



Restaurant



Ticketing




Express



Factory

P810

Mobile Label Printer



Optional



Model name	P810
Print method	Direct thermal
Paper width	79.5±0.5mm
Paper roll diameter	50mm
Paper thickness	0.06 - 0.08mm
Column capacity	576dots/line 512dots/line
Print speed	70mm/s Max.
Interface	Bluetooth
Character size	ANK, Font A:1.5×3.0mm(12×24 dots) Font B:1.1×2.1mm(9×17 dots) Chinese, traditional Chinese:3.0×3.0mm(24×24 dots)
Barcode Character	
Extented character sheet	PC347(Standard Europe) / Katakana/ PC850(Multilingual) / PC860(Portuguese) / PC863(Canadian-French)/ PC865(Nordic) / West Europe/ Greek/ Hebrew/ East Europe/ Iran/ WPC1252/Pc866(Cyrillic#2) / PC852(Latin2)/ PC858/ IranII/ Latvian/ Arabic/ PT151(1251)
Barcode types	1D:UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/ CODABAR/CODE93/CODE128 2D:QR CODE/PDF417
Power	
Power adaptor	Input: AC 110V/240V, 50 ~ 60Hz, Output : DC 9V/2A.
Printer input	DC 9V/2A
Battery	7.4V/2000mAh
Physical characteristics	
Gross weight	325g
Dimensions	136×116×60mm (D×W×H)
Environmental Conditions	
Operation environment	5 ~ 40°C (41~104°F) , Humidity: 25 ~ 85% no condensing
Storage environment	-40 ~ 60°C (-40~140°F) , Humidity: 10 ~ 90% no condensing
Buffer	
Input buffer	32k bytes
NV Flash	64k bytes
Software	
Emulation	ESC/POS
Driver	Windows/Linux/Android/Mac
Utility	Windows & Linux test Utility
SDK	iOS/Android/Windows



ΚΑΡΑΦΥΛΛΗΣ ΣΥΣΤΗΜΑΤΑ ΠΛΗΡΟΦΟΡΙΚΗΣ