

- Sleek and thin design with “Built for Touch” Reliability
- 60% Energy Savings using LED Technology
- 3 Year Standard Warranty
- Integrated cable management
- Space-saving design



1517L 15-inch LED Desktop Touchmonitor

Specifications	
Model	1517L
Color	Black or White
Active Display Area	11.97 x 8.98 inches / 304 x 228 mm
Monitor Dimensions (with stand)	14.1 x 7.8 x 12.5 inches / 358 x 197 x 319 mm (dimensions vary with stand position and options selected)
Monitor Thickness	1.7 inches / 43 mm panel depth
LCD Technology	Active matrix TFT LCD with LED backlighting
Diagonal Size	15.0"
Aspect Ratio	4:3
Native (Optimal) Resolution	1024 x 768
Other Supported Resolutions	640 x 480 @ 60Hz, 75Hz; 720 x 400 @ 70Hz; 800 x 600 @ 56Hz, 60Hz, 75Hz; 1024 x 768 @ 60Hz, 75Hz
Colors	16.2 million
Brightness (typical)	LCD Panel: 250 nits; AccuTouch: 200 nits; IntelliTouch: 225 nits; IntelliTouch ZB: 225 nits; IntelliTouch Pro pcap: 225 nits
Response Time – Total (typical)	16 msec
Viewing Angle (typical)	Horizontal: +/-80° or 160° total; Vertical: +/-70° or 140° total
Contrast Ratio (typical)	700:1
Video	Analog VGA on Female DE-15 connector Input Video Horizontal Sync frequency range: 31.5-60KHz Input Video Vertical Sync (frame rate) frequency range: 56-75Hz
Power	Monitor input power connector - AC: IEC 60320 C6. Monitor input power signal specifications: 100-240VAC, 50/60Hz Monitor input power connector - DC: Coaxial power jack (2.1mm pin outer diameter, 6.4mm barrel inner diameter); Monitor input power signal specifications: 12VDC ±5% Note: Optional AC-DC power adapter sold for this monitor. Adapter input connector: IEC 60320 C14 Adapter input voltage range: 100-240VAC, 50/60Hz; Power Consumption (Typical): ON (monitor): 12W; SLEEP (monitor): 1.0W; OFF (monitor): 0.8W
Weight (with stand)	Unpackaged: 4.3 kg / 9.5 lb; Packaged: 7.3 kg / 16.0 lb.
Shipping Dimensions	19.2 x 9.1 x 19.1 inches / 487 x 231 x 485 mm
Mounting Options	75 mm VESA mount, capped through-mount holes
On-Screen Display (OSD) Controls (Accessible through switches Along the bottom)	Controls: Menu, Up, Down, Select Settings: Brightness, Contrast, Clock, Phase, H- position, V-Position, Auto-Adjust, Aspect Ratio, Sharpness, Color Temperature, OSD Timeout, OSD Language, Recall Defaults Languages: English, French, Italian, German, Spanish, Simplified Chinese, Traditional Chinese, Japanese Lockouts: OSD, Power
Temperature	Operating: 0 °C to 40 °C /32 °F to 104 °F; Storage: -20 °C to 60 °C /-4 °F to 140 °F
Humidity (non-condensing)	Operating: 20%-80%; Storage: 10%-90%
Regulatory approvals and declarations	Argentina S-mark, Australia C-Tick, Canada cUL, IC, China CCC, Europe CE, Japan VCCI, Korea KCC, e-Standby, Mexico CoC, Taiwan BSMI Mark, United States UL, FCC, International CB, RoHS, China RoHS, WEEE, IMERC
Touch Interface	Serial (RS232) and USB
Warranty	3 years standard
MTBF	50,000 hours demonstrated