


## CG2 Barcode Εκτυπωτής

Ασυναγώνιστη απόδοση, ευκολία και ευελιξία

Πολύ αξιόπιστος αντιμικροβιακός εκτυπωτής της σειράς GS2 για την τήρηση της ασφάλειας της υγείας, με εύκολο χειρισμό και προσιτή τιμή. Διατίθεται με τεχνολογία απευθείας θερμικής εκτύπωσης ή θερμικής μεταφοράς.



### Εφαρμογές:



Κατασκευή



Transport &  
Logistics



Λιανική  
πώληση



Βιομηχανίες  
φαγητού



Υγεία



Εστιατόρια

# CG208/ CG212 Τεχνικές Πληροφορίες

PRINTING SPECIFICATION		CG208	CG212
Printing Method		Direct Thermal / Thermal Transfer	
Print Resolution, dots/mm (dpi)		8 dots/mm (203dpi)	12 dots/mm (305dpi)
Max. Print Area	Width, mm (inch)	56mm (2.20")	56mm (2.20")
	Length, mm (inch)	600mm (23.60")	400mm (15.75")
Print Speed, mm/sec (ips)		Up to 100mm/sec (4 ips)	
CPU		32 bit RISC	
Printer Memory		Flash ROM: 4MB, RAM: 8MB	

CONSUMABLES SPECIFICATION (Recommended to use printer supplies manufactured or certified by SATO)			
Sensor Type		I-Mark Sensor (Reflective), Label Gap Sensor (Transmissive)	
Media Type		Roll or fan-fold die cut labels, Plain paper face stock, Synthetics and Continuous stock	
Media Thickness		0.06 – 0.19mm (0.002" – 0.007")	
Label Shape	Diameter	Max. outside diameter: Ø 130mm (5.12"), Core diameter: Ø 25.4mm (1") or Ø 38.1mm (1.5")	
	Wind Direction	Face-in/out	
Label Size	Continuous	Width	12 – 60mm (0.47" – 2.36")
		Length	6 – 600mm (0.24" – 23.6")
	Tear-Off	Width	12 – 60mm (0.47" – 2.36")
		Length	12 – 600mm (0.47" – 23.6")
	Cutter	Width	12 – 60mm (0.47" – 2.36")
		Length	22 – 600mm (0.87" – 23.6")
	Dispenser	Width	12 – 60mm (0.47" – 2.36")
		Length	22 – 100mm (0.87" – 3.94")
Ribbon	Size	Width: 59mm (2.32") Max. Length: 100m (328')	
	Core Diameter	Ø 12.7mm (0.5")	
	Wind Direction	Face-out	

FONTS / SYMBOLOGIES		
Fonts	Standard Fonts	Bitmap Fonts Alphanumeric and Symbol: WB (18x30 dot), WL (28x52 dot), XU (5x9 dot), XS (17x17 dot), XM (24x24 dot), XB (48x48 dot), XL (48x48 dot), OCR-A (15x22 dot), OCR-A (22x23 dot), OCR-B (20x24 dot), OCR-B (30x36 dot)
	Rasterized Fonts	CG Times, CG Triumvirate
Barcode	1D Barcode	UPC-A/E, JAN/EAN-8/13, Code 39, Code 128, GS1-128 (UCC /EAN128), Codabar (NW-7), Interleaved 2 of 5, Bookland (2/5 char add-on code), GS1 Databar (RSS14), Composite JAN/EAN-8/13; Composite UPC A/E; Composite GS1 128/CC
	2D Barcode	PDF417 (Ver2.4), MAXI Code (Ver3.0), QR Code, GS1 Data Matrix (ECC200)
Print Rotation	Character Data / Barcode	0°, 90°, 180°, 270°

COMMUNICATION INTERFACES	
Interface	USB + RS-232C* model, USB + LAN model, Optional: External SATO Wireless LAN**
Command	SBPL (Ver 4.2) SATO Barcode Printer Language

OPERATING CHARACTERISTICS		
Power Requirements		Input voltage adapter: AC100V-240V (auto switching)/40W (peak) – Input voltage printer: 19V/3A
Environment	Operating	0 – 35°C / 30 – 80% RH (without condensation)
	Storage	-10 – 60°C / 15 – 85% RH (without condensation)
Dimension		(W x D x H): 128 x 235 x 173mm (5.04" x 9.25" x 6.81")
Weight		TT model (approx 1.6 kg / 3.5 lbs), DT model (approx 1.5 kg / 3.3 lbs)

MISCELLANEOUS	
Certifications	Cerner Validated, FCC, UL, CSA, CCC, CE, ROHS compliant, Energy Star™
Anti-microbial Finishing	The material of the casing includes an anti-microbial substance which is tested according to the JISZ2801 standard The anti-microbial casing discourages the growth of bacteria and micro-organisms

OPTIONS	
Accessories	Cutter, Dispenser, SATO Keypad, Unwinder, NiceLabel

\*The RS-232C Interface enables connection to PC or SATO Keypad

\*\*Only possible with the USB + RS232-C versions

SATO makes no guarantee that the above features are available in all models, and specifications are liable to change, without notice. Version 11/17 \* Measurements are approximate values.

© 2020 SATO CORPORATION. All rights reserved.

For more information please contact your SATO representative or visit our website