

OK-K1 KIOSK

High Performance with contemporary design!
Improve your customers experience today!



21.5 Inch front
electrostatic touch panel



3" thermal printer



Barcode Scanner

Make an advance payment platform as the **KIOSK** of the OKPOS! Mini-Size is a good fit to set very effectively anywhere. Structured to put stand or the surface of a wall. More clear display with 21.5" Full HD, tiny and simple Barcode Scanner 1D/2D, and 3" thermal printer is contained the one platform.

OKPOS' KIOSK makes an epoch your business as the order and pick up system!





High Performance with contemporary design!
 Improve your customers experience today!

OK-K1



Inside I/O Interface



minimal and cute size



Barcode Scanner



3" thermal printer

Specification for OK-K1

Item	Specification	
SYSTEM	Processor	Intel® Celeron® J1900 (2M Cache, 2.0 GHz) Intel® Celeron® 3955U (2M Cache, 1.70 GHz) Intel® Core™ i3-7100U (3M Cache, 2.4 GHz) / Intel® Core™ i7-7500U (4M Cache, 2.7 GHz)
	Graphic	Integrated Intel® HD Graphics engine
	Memory	4GB(up to 8GB) DDR3L or DDR4 SO-DIMM x 1
	Storage	2.5" SSD or HDD
	OS	Windows 7, Windows 10, POSReady 7, Win10 IoT
	Audio	Stereo Max 4W x 2
Display	Type	21.5" FHD LCD
	Resolution	1080 X 1920
	Brightness	250~300 cd/m ² (typ.)
	Touch	Projective Capacitive Touch(Multi 10 Point)
Interface	System Port	1x DC-12V 4-pin Power Input Connector, 1x DC-12V 2-pin Power Output Jack, 1x VGA Port, 1x PS/2 Keyboard/ Mouse Connector, 1x Ethernet Port, 3x USB 2.0 Port, 1x USB 3.0 Port, 1x Serial Port (RS-232/422/485), 2x Serial Port (RS-232), 1x Audio Jack (Line-out)
	Rear Port	Shared with M/B system port USB x 1(2.0), Serial x 2(RJ50), LAN x 1(RJ45)
	Printer	3" Thermal Printer with Autocut Max 200mm/sec, 80mm Roll
	Body	330mm (W) x 280mm (L) x 741mm (H)
	Stand	420mm (W) x 400mm (L) x 898mm (H)
Option	Card Reader	Magnetic Stripe Reader(MSR) Comply with ISO 7811, Track 1,2,3
	Barcode	1D/2D Barcode Scanner

