



P323B

- Support direct USB charging;
- Long lasting battery life;
- Dual mode bluetooth;
- OLED screen available;
- TSPL, EPL, ZPL, DPL, CPCL, ESC/POS command compatible.

APPLICATIONS



Shopping



Mart



Hospital



Coffee Shop




Restaurant



Ticketing

P323B

Mobile Label printer



MODEL	P323B
Printing Method	Direct Thermal
Resolution	8 dots/mm(203 DPI)
Interface	USB+Bluetooth / USB+WIFI
Real Time Clock	Standard
Max Print Speed	70mm/s (2.7"/s)
Max Print Width	72mm (2.8")
Max Print Length	1778mm(70")
Media Type	Continuous, gap, black mark;
Media Width	20 mm ~ 76 mm
Media Thickness	0.06 mm ~ 0.08 mm
Media Length	10 mm ~1778 mm
Label Roll Capacity	50mm (Diameter)
Memory	8MB Flash Memory 8MB SDRAM Micro SD card reader for Flash memory expansion, up to 4GB
Sensor	Gap sensor Printer Head opened sensor Black mark sensor Paper end sensor
Processor	32-bit RISC CPU
Power Supply	Input: AC 100-240V; Output: DC 9V/2A
Barcode	1D barcode: Code128 subsets A.B.C,Code128UCC, EAN128, Interleave 2 of 5, Code 39,Code 93, EAN-13, EAN-8, Codabar, POSTNET, UPC-A, UPC-E, EAN and UPC 2(5) digits, MSI, PLESSEY, China Post, ITF14, EAN14, Code 11, TELPEN, PLANET, Code 49, Deutsche Post Identcode, Deutsche Post Leitcode, LOGMARS 2D barcode: DataMatrix, Maxicode, PDF-417, QR code;
Emulation	TSPL-EZ (EPL, ZPL), DPL, CPCL, ESC/POS
Dimension	124mm*108mm*61mm (W*H*D)
Weight	357.3 g
Power	Output: AC 9V-2A
Battery	7.4V / 2500mAh
Safety Standard	Operation condition: 5 ~ 40 °C (41 ~ 104 °F) ,25 ~ 85% non-condensing
Environment	Storage condition : -40 ~ 60 °C (-40 ~ 140 °F), 10 ~ 90% non-condensing

