



POS

True Flat POS Workstation



- 15inch LED Back-lit Display
- Variety of configurations: J1900, I5-3337U
- Frame or True-Flat Front Bezel
- Resistive or Projected Capacitive Touchscreen

- LCD / VFD customer display
- 10.1inch Second Display
- Removable SSD
- Aluminum Stand with Cable management



**MSR &
Dallas Key**



USB Ports



**Customer
Display**



I/O Panel

SPECIFICATIONS

	POS J1900	POS i5
Display	15.1" LED Back lit, 4:3 Ratio	15.1" LED Back lit, 4:3 Ratio
Touch Panel	Resistive Touch / Projected Capacitive Touch	Resistive Touch / Projected Capacitive Touch
Chipset	Intel Celeron Chipset	Intel NM70 Chipset
Frame	Frame / True Flat	Frame / True Flat
Master board	Fan-less J1900	I5-3337U with Fan
CPU	Intel® Celeron® Processor J1900 (2M Cache,2 GHz)	Intel i5-3337 Dual core 1.7Ghz
RAM	Standard 2G DDR3 1333, 1* SO-DIMM DDRIII 800/1066MHz'. Max. Up to 4GB - 8GB	Standard 2G DDR3 1333, 1* SO-DIMM DDRIII 800/1066MHz Max. Up to 4GB - 8GB
Storage	128G SSD	128G SSD
Video card	Intel HD Graphics	Intel HD Graphics
Network card	RTL8111E	RTL8111E
Watch Dog Timer	NA	NA
Sound card	Realtek ALC662	Realtek HD ALC662
Rs232 COM ports	2	2
RS485	Optional	Optional
HDMI	Optional	1
USB	6	4
PS2 Mouse	-	1
PS2 Keyboard	-	1
LPT / Parallel	1	Optional
LAN	1	1
VGA	1	1
Environmental conditions		
Operating Temp	-10°C - +60°C	-10°C - +60°C
Operating Humidity	0% RH - 95%	0% RH - 95%
Storage Temp	-20°C - +70°C	-20°C - +70°C
Storage Humidity	10% RH - 90% RH	10% RH - 90% RH
Packaging Dimensions	8kg	8kg
System Size	35.6*29*36cm	35.6*29*36cm