

Touch LCD Monitor

TM-120/TM-150

TM-170/TM-190

A Touch Monitor

Meets All Your Needs



Features

- Tilt Angle 0° ~ 90°: Adapt to operation in any environment.
- Available with different touch panel technology (5-wired resistive, SAW, and Capacitive)
- With rugged and solid base design
- User-friendly manipulation
- Exceptional cable management
- Choice of 12", 15" and 17" and 19" TFT LCD panel
- Water Spills resist
- Optional Integrated 3-Track MSR and/or Customer pole display
- OSD and Power Switch Control panel on the rear
- With Dual VGA Interface (VGA and DVI)
- With USB or RS-232 Touch Interface
- Hidden Power Adapter Design
- Removable base and Wall Mounting Capability 75mm VSEA holes

MODEL	TM-100	TM-120	TM-150	TM-170	TM-190
Display Type	Active Matrix TFT LCD				
LCD Size	10.4"	12"	15"	17"	19"
Display Area (mm)	211.2 (W) x 158.4(H)	245.76 (W) x 184.32(H)	340 (W) x 228 (H)	338 (W) x 270 (H)	376.32 (W) x 301.056 (H)
Max. Resolution	800 x 600	1024 x 768	1024 x 768	1280 x 1024	
Colors	16.7 million				
Brightness	250 cd/m ² (Typ.)	150~ cd/m ² (Typ.)	250 cd/m ² (Typ.)	250 cd/m ² (Typ.)	250 cd/m ² (Typ.)
Contrast Ratio	400:1	250:1	300~400:1	450:1	400:1
Input Connector	D-SUB 15 PIN Female / 24 PIN DVI				
Power Supply	12V / 3A External Power Adapter				
Color	Black Color	Black or Silver Color			Black Color
Dimension (W x H x D)	250x240x185mm	304x270x199mm	378x348x226mm	418x378x226mm	418x378x226mm
Temperature	Operation : 0°C to 40°C (Environment)				
Humidity	10% to 90%				
Touch Panel	TW 5-wire or ELO Resistive Touch Panel (RS-232 or USB)				
Optional Device	VFD Customer Display, MSR Card Reader Second 12"/15"/17" LCD Screen with or without Touch Screen				

