SUNMI D2s PLUS COMBO Smart Desktop Terminal

A one-stop choice for your retail checkout.



A more powerful printer inside

A desktop terminal that prints at 250mm/s* definitely will be your great helper at peak hours. The 80mm wide receipts give you more room for your creative ideas that show your brand personality, no matter by long texts or images, or combined.

A cash drawer and a keyboard included

Customize your function keys on the 89-key POS keyboard to speed up your checkout. A cash drawer also was built in the COMBO for your cash payment businesses.

A printer that "feels" smoothes your business operations

The newly added sensors for paper jam, paper pickup, out of paper and overheated motor can effectively protect the printer and also delivers smooth receipt printing experience.

More configuration options

Three display options. Find what combination works best for you.

Display Options

15.6" Single 15.6"FHD,1920*1080



15.6" +10.1" Main 15.6"FHD,1920*1080 Secondary 10.1"FHD, 1024*600



15.6" +15.6" Main 15.6"FHD,1920*1080 Secondary 15.6"FHD,1920*1080









SUNMI D2s PLUS COMBO Tech Specs

Model Approved OS CPU Memory L1551 L1552 L1553 2GB RAM+16GB ROM Display Printer Bluetooth Ports Built-in 80mm thermal Config 1: 1* RJ11 port 1* RJ12 cash drawer port Main: 15.6" FHD, 1920*1080 Capacitive multi-touch screen 2.1/3.0/4.2 Config 2: Main: 15.6" FHD, 1920*1080 Capacitive multi-touch screen Secondary: 10.1" HD, 1024*600 Capacitive multi-touch screen 1* RJ45 LAN 1* 3.5mm audio jack Max paper roll diameter: 1* Power port 1x Micro-USB debug port Config 3: Main: 15.6" FHD, 1920*1080 Capacitive multi-touch screen Secondary: 15.6" FHD, 1920*1080 Capacitive multi-touch screen 80mm

Ethernet **IAN 100M**

Button 1* Power (lock screen) key

Dimensions (L*W*H) Config 1: 381.73*331.6*498.03mm Config 2: 381.73*349.08*498.52mm Config 3: 381.73*369.61*525.52mm

Keyboard

Type-C USB

Weight

Up to 64G

Config 1: 7.0kg Config 2: 7.770kg Config 3: 8.695kg

External Memory Card

Wi-Fi support IEEE 802.11 b/g/n

Environment Working temp.: 0°C~40°C Storage temp.: -20°C~60°C Speaker

Power Adapter Input: AC100 ~ 240V/1.7A Output: DC24V/2.5A

Cash Drawer and 3 coin trays 9V-24V

1.The usable memory may be less than the installed memory.