



Specifications	iSPOS 5S
Processor	Intel Core i3-6100U, 2.30 GHz
System Memory	2*SO-DIMM, DDR4 2133, Max. 32 GB
Display	15" TFT LCD, 1024*768
Touch Screen	Projected Capacitive Touch or 5-wire Resistive Touch
Operation System	Win 7, POSReady 7, Win 10 IoT 64 bit
Storage	1*SATA III for 2.5" 9.5 mm SSD/HDD 1*SATA III for internal Half-Slim SSD 1*SATA III for internal mSATA SSD Support RAID 1 Disk Mirroring
External I/O Ports	
USB port	4*USB2.0
Serial port	2*DB-9 (COM3/COM4)
Cash Drawer	1*RJ-11 (COM5)
Keyboard	1*PS/2
LAN port	1*RJ-45 (10/100/1000 Mbps)
VGA or Parallel	1*DB-15 or 1*DB-25
Others	2*Built-in Speakers, 1*Mic, 1*Line out
Mechanical & Environment	
Dimensions & Weight	389(W)*232(D)*369(H) mm, 8.5 Kgs
Safety Certifications & IP Rating	FCC/CE, IP 66 Compliance
Storage & Operating Temp.	-20°C ~ 60°C, 0°C ~ 40°C
Relative Humidity	10% ~ 90% (non-condensing)
Power Consumption	60 W maximum
Peripheral Options	
Wireless LAN	802.11 b/g/n
Customer Display	SENIOR iSMON8 series or VFD 20*2 lines Display
Magnetic Card Reader	Single Track, Double Tracks, Triple Tracks
Identification Devices	RFID (ISO/IEC 14443A/13.56 MHz/Mifare S50)
	Fingerprint Reader
	i-Button